

## CWT Experimental 3D Printed Carriage



[VIEW IN BROWSER](#)

updated 9. 4. 2024 | published 9. 4. 2024

### Summary

Designed to be strong and lightweight. Direct-Screw in with no heated inserts. 5mm Thickness LM8UU Variant EXPERIMENTAL

[Hobby & Makers](#) > [Mechanical Parts](#)

Tags: [printed](#) [carriage](#) [sv06](#) [sv06sovol](#)

**EXPERIMENTAL!**

I will need feedback on how this performs!

LM8UU Variant only for now. Designed to be a drop-in replacement for the SV06 Carriage for lightweight 4x LM8UU Bearing add-on to improve stability, and prevent rod deformation due to homing.


Please PM or leave a comment on how effective this is.

Recommend at least 7 walls in PETG/PLA/ASA/ABS for low speed testing.

Otherwise print in Carbon Fiber composite for ideal rigidity. THE MORE WALLS THE BETTER

**EXPERIMENTAL!**

# Model files



**cwt-exp-printed-carriage.stl**

❏ EXPERIMENTAL

## License

This work is licensed under a  
[Creative Commons \(4.0 International License\)](#)



**Attribution-NonCommercial**

---

- ✘ | Sharing without ATTRIBUTION
- ✔ | Remix Culture allowed
- ✘ | Commercial Use
- ✘ | Free Cultural Works
- ✘ | Meets Open Definition